

VistaClear™ DP

Centralized Waterline Treatment System



Powerful protection and convenience, centralized.

The VistaClear™ Centralized Waterline Treatment System provides filtered procedural water directly to dental operatories—eliminating the need for bottle systems and storage tanks! The system's micron-level filtration, built-in backflow prevention and patented method for waterline cleaning save practices time and money while protecting dental equipment.


The DentaPure™ Cartridge and carbon block filter are used with the VistaClear™ DP Centralized Waterline Treatment System.

DentaPure™ Cartridge

The EPA-registered DentaPure™ Cartridge provides safe and compliant dental unit water for up to 10 operatories for 365 days (or 2,400L of water, if usage records are kept), ensuring practices meet or exceed water quality with a maximum of 200 CFU/mL.



CVV1000-DP



⌚ Saves time

The system's on-demand filtration eliminates wait time and the need for storage tanks and bottle systems. And its onboard DentaPure™ Cartridge eliminates the need for regular shocking protocols to make waterline maintenance much easier and more efficient.

🐷 Saves money

The system includes QAI-certified backflow preventers that eliminate the need for reduced pressure zone (RPZ) devices and the ongoing cost of annual inspections. It also eliminates the need for purchased water and daily maintenance products.

🛡️ Protects equipment.

With micron-level filtration and no harmful chemicals, the system protects expensive handpieces and turbines from the wear-and-tear typical water supplies can inflict. The system removes virtually all contaminants that often reside in city water supplies.

Crosstex is now a proud member of

HuFriedyGroup
The Best In Practice

VistaClear™ DP Centralized Waterline Treatment System



Source Water Input Specifications

Operating

Temperature Range

45 to 100°F (7.22-37.78°C)

Operating Pressure Range

40 to 100 psi (2.07-6.89 bar)

Maximum Influent

Chlorine / Chloramine

5 ppm

Maximum Continuous

Flow Rate / Filter

0.2 gpm (0.76 Lpm)

Additional Information

Filter Element Service Life

12 months

Filter and Cartridge Requirements

DP365VC(CA) DentaPure™ Cartridge CVR9725 Carbon Block Filter

Dimensions (W x H x D)

16 in x 24 in x 5 7/8 in

Approximate Ship Weight

28 lbs.

Installation Requirements

System requires access to cold, potable water supply, compressed air and drain connection. Electricity is NOT required.

Use only 1/4 in O.D. (soft) copper tubing for dedicated lines to each operator. If copper tubing is unable to be installed for some reason, use only 1/4 in O.D. LLDPE tubing. Do NOT use standard plumber's PEX tubing, which is usually 3/8 in O.D. Do not exceed 90 ft in length for runs to any operator.

- i** Use of a VistaClear™ Centralized Waterline Treatment System does not, by itself, eliminate the need for proper user maintenance. Due to the nature and complex design of dental delivery units, the periodic use of waterline cleaners and antimicrobials is extremely important for proper dental waterline care. For this reason, Crosstex makes specific bacteria-reduction claims for output water from dental delivery units connected to DentaPure™ Cartridges. To obtain maximum bacteriological reduction, dental unit waterlines are to be cleaned with an approved dental unit waterline agent prior to initial installation of DentaPure™ Cartridges.



For more information visit [HuFriedyGroup.com](https://www.HuFriedyGroup.com)

Hu-Friedy Mfg. Co., LLC, 1666 E. Touhy Ave., Des Plaines, IL 60018 | [HuFriedyGroup.com](https://www.HuFriedyGroup.com)

All company and product names are trademarks of Hu-Friedy Mfg. Co., LLC its affiliates or related companies, unless otherwise noted. Marks not registered in all jurisdictions.

©2023 Hu-Friedy Mfg. Co., LLC. All rights reserved. HFL-831/0723

Crosstex is now a proud member of

